GOEBEL

Alprinta







substrates: paper, labels, film substrate range: film: 10µ - 350µ

web width: 520, 740

size range: film: $20" - 28^{1/3}"$ paper: 17" - 36" on special request up to 40" in increments of: 0.1 mm 1/3" or 1/4" o

printing technologies: Offset printing: based on size variable cassettes:

film: VOI = variable offset insert, with separate servo driven plate & blanket cylinder, light weight format cylinders can be ex-

paper: 28-250g/m²

changed manually and tool less

paper: 3 cylinder gear driven offset cassettes

Flexo printing: Flexo unit with anilox and cliché sleeve

for UV, water or solvent based inks

plus integrable aggregates: silk screen & rotogravure printing, inkjet, processing cassettes:

plus integrable aggregates: silk screen & rotogravure printing, inkjet, die cutting, cross perforation, sprocket-hole – and file-hole punching

converting mode: reel to reel, reel to sheet, reel to fold

curing technology: UV; EB curing; hot air for water or solvent based inks

drive system: servo drive technology

applications: commercial work, mailings, security printing, pharma printing, labels,


covers, packaging


OEM equipment: remote ink key control

register control system web video system 100% inspection

silk screen unit, rotogravure unit, Inkjet

Modular platform with big format range up to 40" for high quality commercial work and pharma printing. Can be equipped with special VOI cassettes for printing flexible packaging.







Typical application



Check List

customer name: address:	
application traditional printing: packaging printing: special applications: paper/film:	
number of units offset printing: miscellaneous units:	
curing technology UV curing: EB curing: Hot air dryer:	
processing die cutting: cross perforation: sprocket-hole punching: file-hole punching:	
converting stop unwind/rewind: non/stop unwind/rewind:	
miscellaneous	
place: date: name:	

Please, return to:

Goebel Capital Schochenmühlestr. 4 6430 Baar Switzerland info@goebel-capital.com