GOEBEL

Novaprint



substrates: labels, film, paper, cardboard

substrate range: 50μ - 250μ (special range on request)

web width: 520, 680, 760

size range: 17" - 28" (special sizes on request)

printing technologies: offset printing based on size variable cassettes,

plus flexo printing, silk screen printing, gravure printing die cutting, cross perforation, sprocket-hole punching

processing: die cutting, cross perforation, sprocket-hole

converting mode: reel to reel, reel to sheet, reel to fold

curing technology: UV, (EB curing on request) drive system: servo drive technology


applications: traditional printing, security printing and high quality applications

OEM equipment: remote ink key control

register control system web video system 100% inspection

closed loop color control

Latest state-of-the-art offset printing unit, with advanced printing quality, less waste and minimum set-up time, designed for high productivity and optimum efficiency.



Novaprint print unit (double ink tray optional)



typical application (tax stamps)



Check List

customer name: address:	
application traditional printing: security printing: special applications: paper:	
number of units offset printing: flexo printing: gravur printing:	
Curing technology UV curing: EB curing (optional):	
processing die cutting: cross perforation: sprocket-hole punching:	
converting stop unwind/rewind: non/stop unwind/rewind:	
miscellaneous	
place: date: name:	

Please, return to:

Goebel Capital Schochenmühlestr. 4 6430 Baar Switzerland info@goebel-capital.com